



Anteya Power Corp. Product Specs

ITEM		ANP-G IP20				
Downlight IP20 for In Door use series						
Module No.	ANP-G8-A	ANP-G15-A	ANP-G21-A	ANP-G30-A	ANP-G40-A	
Power Specs						
Voltage	100-240Vac	100-240Vac	100-240Vac	100-240Vac	100-240Vac	
Current	STD	STD	STD	STD	STD	
Power	8W	15W	21W	30W	40W	
Power Factor	0.9	0.9	0.9	0.9	0.9	
Life Span	30,000hrs	30,000hrs	30,000hrs	30,000hrs	30,000hrs	
Size	D115*H45mm	D130*H50mm	D160*H60mm	D190*H60mm	D230*H75mm	
Cut Out	Φ 105(3")	Φ 115-120(4")	145-150(5")	170-180(6")	205-220(8")	
Beam Angle	60°	60°	60°	60°	60°	
CRI	Ra>80	Ra>80	Ra>80	Ra>80	Ra>80	
IP Protection	IP20	IP20	IP20	IP20	IP20	
Environment Specs						
Operation Temp.	-20-50+	-20-50+	-20-50+	-20-50+	-20-50+	
Storage Temp.	-20-50+	-20-50+	-20-50+	-20-50+	-20-50+	
Operation Humidity	10%-90%	10%-90%	10%-90%	10%-90%	10%-90%	
Illumination						
Color Temp. (2700-3200)	600lm	1200lm	1700lm	2400lm	3200lm	
Color Temp. (3800-5500)	650lm	1300lm	1900lm	2650lm	4500lm	
LED chips	Epistar COB	Epistar COB	Epistar COB	Epistar COB	Epistar COB	
Driver	Localized	Localized	Localized	Localized	Localized	