



Anteya Power Corp.
Product Specs

ITEM		ANP-SCW-D				
Flood Light with Die Cast Aluminum						
Wattages	50w	70w	100w	150w	200w	
Type	Bracket	Bracket	Bracket	Bracket	Bracket	
Power Specs						
Voltage	85-265Vac	85-265Vac	85-265Vac	85-265Vac	85-265Vac	
Current	0.5A	0.7A	1A	1.2A	2A	
Power	50W	70W	100W	120W	200W	
Power Factor	0.95	0.95	0.95	0.95	0.95	
Life Span	30,000hrs	30,000hrs	30,000hrs	30,000hrs	30,000hrs	
Weight	2.4kg	2.4kg	6.0kg	6.3kg	10kg	
Beam Angle	120	120	120	120	120	
Install hieght	4mtrs	4mtrs	7mtrs	9mtrs	15mtrs	
IP Protection	IP65	IP65	IP65	IP65	IP65	
Environment Specs						
Operation Temp.	-20-60+	-20-60+	-20-60+	-20-60+	-20-60+	
Storage Temp.	-20-60+	-20-60+	-20-60+	-20-60+	-20-60+	
Operation Humidity	10%-90%	10%-90%	10%-90%	10%-90%	10%-90%	
Illumination						
	5000lm	7000lm	10,000lm	15,000lm	20,000lm	
Nichia LED chips	option	option	option	option	option	
Philips LED chips	option	option	option	option	option	
Driver	MeanWell or Philips	MeanWell or Philips	MeanWell or Philips	MeanWell or Philips	MeanWell or Philips	

